


<b>TASMAN</b> 	DOC TITLE: API 6A Adapter Spool	DOC. No: TAS-RT-ADPSPL-001
	REV: NA	Page   1

<b>API 6A Adapter Spool</b>	
<b>Applications &amp; Benefits</b>  The Adapter Spool is a part which is often used in pressure control applications. Typically the Adapter Spools have different nominal end connections.	
<b>Key Features</b> <ul style="list-style-type: none"> <li>Tasman Oil Tools have a large selection of Adapter Spools in various sizes and pressure ratings used for oilfield applications.</li> <li>Designed and manufactured in accordance with API 6A standards</li> <li>The Adapter Spool can be supplied with material specifications of AISI 4130 or 410SS as per customer's requirement</li> </ul>	
<b>Availability Specification</b>	
Working pressure	2000 PSI - 20000 PSI
Working medium	Oil, Natural Gas, Mud
Working temperature	-46°C -121°C
Material class	AA – HH
Specification class	PSL1 - PSL4
Performance class	PR1 - PR2
Connection	API 6A Flange, API 16A Clamp, WECO Union

The use of the information is based on the readers discretion. No warranty is implied or expressed by Tasman Oil Tools with the use of information contained herein. The information contained in this Data Sheet is subject to revision without notice.