

API 6A Spacer Spool

Applications & Benefits

Tasman Oil Tools have a substantial inventory of API 6A Spacer Spools which are manufactured with a variety of end and outlet configurations based on customer needs.

Key Features

- Flanged, studded, and hubbed ends available, in any combination
- Manufactured for any combination of size and pressure ratings
- Spacer Spools designed to minimize length while allowing sufficient clearance for wrenches or clamps, unless otherwise specified by the customer
- The standard design for Spacer Spools does not include outlets, although outlets can be added as specified
- Available for general service and sour service in compliance with any temperature rating and material requirements specified in API specification 6A
- Available with Stainless Steel 316L or Inconel 625 corrosion resistant alloy ring grooves
- Tap-end studs and nuts are normally provided with studded end connections



Availability Specification

Working pressure	2000 PSI - 20000 PSI
Working medium	Oil, Natural Gas, Mud
Working temperature	-46°C -121°C
Material class	AA – HH
Specification class	PSL1 - PSL4
Performance class	PR1 - PR2
Connection	API 6A Flange, API 16A Clamp, WECO Union

The use of the information is based on the readers discretion. No warranty is implied or expressed by Tasman Oil Tools with the use of information contained herein. The information contained in this Data Sheet is subject to revision without notice.