



DOC TITLE: SPIRAL DRILL COLLAR PERFORMANCE DATA SHEET

DOC. NO. TAS-RT-SDC-004

REV: NA

Page 1 of 1

6.500" SPIRAL DRILL COLLAR PERFORMANCE DATA SHEET

IMPERIAL UNIT

Spiral DC Size & Weight: 6.500" x 2.8126 ID
Material Grade: AISI 4145-H mod.
Length (ft): 31
Connection: NC-50 (4-1/2" IF)

SPIRAL DRILL COLLAR DIMENSIONS & MATERIALS

Technical Details

Outside Diameter (OD)	in	6.500
Inside Diameter (ID)	in	2.8126
Shoulder type	in	18°
Overall Length (New)	ft	31.000
Elevator & Slip recess OD	in	5.000
Elevator & Slip recess	in	66.9
Spiral length	in	235.8

SPIRAL DRILL COLLAR DIMENSIONS & MATERIALS

Technical Details

Box Tong Space	inch	29.5
Pin Tong Space	inch	29.5
Displacement	gal/ft	1.2396
Capacity	gal/ft	0.3227
Closed End Displacement	gal/ft	1.5623
Weight	lbs	2,527
Weight / Length	lbs/ft	81.52

Connection

Connection Type		NC-50
Outside Diameter (OD)	in	6.500
Inside Diameter (ID)	in	2.8126
BB+SRG		Yes
Connection Tensile Strength	lbs	1,234,000
Con.Torsional Strength	ft-lbs	50,800
Make-Up Torque	ft-lbs	28,800
Bending Strength Ratio (BSR)		2.19

Body

Material Grade		AISI 4145-H mod.
Tensile Capacity (New)	lbf	1,476,000
Torsional Capacity (New)	ft-lbs	116,800

The use of the information is based on the readers discretion. No warranty is implied or expressed by Tasman Oil Tools with the use of information contained herein. The information contained in this Performance Data Sheet is subject to revision without notice.